

T-SERIES ACTUATOR®

This series of powerful robot actuators allows engineers, researchers, and industrial integrators to quickly and easily create world-class custom robots of any configuration. T-Series Actuators® are packed with sensors that enable controllable position, velocity, and sensitive torque control as well as three axis inertial measurement.

Each actuator is a series-elastic actuator that integrates a brushless motor, gear train, spring, encoders, and control electronics into a compact package that runs on anything from 24V-48V DC and communicates using standard 10/100Mbps Ethernet.



The T-Series Actuator® is designed to function as a full-featured robotic component as opposed to a simple servo motor. The output rotates continuously, requires no calibration or homing on boot-up, and contains a thru-bore for easy daisy-chaining and wiring. This enables these actuators to be used in everything from wheeled robots to multi-degree of freedom collaborative robotic arms.

HEBI Robotics provides cross-platform software tools that make configuring and controlling the T-Series a breeze, with features such as live plotting, APIs for MATLAB, ROS, C/C++, and Python.



T-SERIES ACTUATOR – TECHNICAL SPECIFICATIONS

CONFIGURATION	T5-1	T5-4	T5-9	T8-3	T8-9	T8-16
Peak Torque	2.5 N-m	7 N-m	13 N-m	7 N-m	20 N-m	38 N-m
Cont. Torque	1.3 N-m	4 N-m	8 N-m	3 N-m	8 N-m	16 N-m
Max Speed	90 RPM	32 RPM	14 RPM	84 RPM	30 RPM	15 RPM
Mass	450g	450g	450g	575g	575g	575g
Dimensions (w/ connector cover)	126mm x 74mm x 34mm 15mm hollow bore			126mm x 74mm x 48mm 15mm hollow bore		
Power	24-48V DC Cont. Current: 0.5 A @ 36V Peak Current: 1.6 A @ 36V			24-48V DC Cont. Current: 1.3 A @ 36V Peak Current: 3.0 A @ 36V		
Temperature	-10°C to 50°C Ambient					
Communication	2x 100 Mbps Plastic Optical Fiber (OptoLock ®)					
Angular Resolution	0.005°					
Torque Resolution	0.01 Nm					
Backlash	+/- 0.25°					
Sensing	Angular Position (multi-turn absolute, +/- 4 turns) Angular Velocity Output Torque 3-axis Accelerometer / Gyro Temperature Voltage Current					
API Support	MATLAB (Windows / Linux / OS X) ROS (Linux) Python (Windows / Linux / OS X) C/C++ (Windows / Linux / OS X)					
<p>Each individually purchased T-Series Actuator® includes: A-2456-02: R/T-Series Standard Wiring Kit Additional technical documentation at docs.hebi.us</p> <p>Updated on Jan 29, 2024. Specifications subject to change without notice.</p>						



3577 Bigelow Blvd, Pittsburgh, PA 15213

hebirobotics.com | info@hebirobotics.com